



PRODUCT DATA SHEET

GOLD SL **Automotive Engine Oil**

20W50 SL/CF
Code:104

GOLD SL is best suited for use in petrol powered engines. Under normal service conditions it will provide good protection from piston deposits, prevent oil thickening and sludge build up.

SPECIFICATIONS

GOLD SL meets or exceeds the following specifications.

- API SL/CF
- CCMC G4, D4, PD-2
- SAE 20W50
- US MILITARY - MIL-L-46152D

APPLICATIONS

GOLD SL is suitable for petrol, diesel and LPG fuelled vehicles that require and SL rated engine oil.

GOLD SL is also suited for vehicles fitted with turbo charges.

GOLD SL will provide a high level of protection against wear, sludge formation and acid corrosion.

GOLD SL assists in maintaining engine cleanliness and will provide anti wear protection compared to standard SF and SJ rated oils.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	20W50
Specific gravity at 15C	0.9
Viscosity at 40C, mm ² /s (cSt)	160
Viscosity at 100 C, mm ² /s (cSt)	180.3
Viscosity index	128
TBN mgKOH/g	7.1
Flash Point C	245

PACKAGE SIZE 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.