



PRODUCT DATA SHEET

MAXIVIS

Automotive Engine Oil

15W50 SM/CF

Code: 106

MAXIVIS is a true multi functional oil representing a new generation providing better protection from piston and sludge deposits, reduces oil thickening and exceptional anti-wear protection.

SPECIFICATIONS

MAXIVIS meets or exceed the following specifications.

- API SM/CF
- SAE 15W50
- DAIMLER BENZ DB 229.1
- US MILITARY - MIL-L- 46152E, 21046
- CCMC G4, D4, PD2
- ACEA A3/B3

APPLICATIONS

MAXIVIS motor oil is suitable for all late vehicles including those fitted with turbo chargers and ideal for use in L.P.G. fuelled vehicles and diesel engines where an API CF performance is stipulated or MIL-L-21046 level of performance is specified.

MAXIVIS meets or exceeds the requirements of an SM/CF engine oil and provides a high level of protection against wear, sludge formation and acid corrosion.

MAXIVIS assists in maintaining engine cleanliness and additionally assists in energy conservation and fuel economy and providing exceptional anti-wear protection and has a high viscosity index, ensuring circulation of oil to all moving parts during cold weather start ups and providing additional protection during this critical time of an engines operation.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	15W50
Specific gravity at 15 c	0.88
Viscosity at 40c, mm ² /s (cSt)	150
Viscosity 100c, mm ² /s (cSt)	18
Viscosity index	130
TBN, mgKOH/g	9.1
Flash Point C	245

PACKAGE SIZE 5 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.