



PRODUCT DATA SHEET

RUN IN OIL Automotive Engine Oil

SAE 30 SF/CC

Code:114

RUN IN OIL is a monograde SAE 30 oil for use in petrol and diesel engines which have been reconditioned with new pistons, cylinder liners, bearings, valves and guides.

SPECIFICATIONS

RUN IN OIL meets or exceeds the following specifications.

- API SF/CC
- CCMG2
- SAE 30
- US MILITARY - MIL - L -46152C

APPLICATIONS

RUN IN OIL is suitable for the lubrication of all types of reconditioned engines during the run-in period which usually is between 3000 km and 5000 km or less depending on the recommendation of the engine reconditioned.

RUN IN OIL is suitable for running-in engines, L.P.G. fuelled engines and diesel engines which ensures the bedding-in process of all moving parts for a long trouble free life with minimum oil consumption.

RUN IN OIL meets or exceeds the requirements of an SF/CC engine oil and provides a high level of protection against wear, sludge formation and acid corrosion during the run-in period.

RUN IN OIL assists in maintaining engine cleanliness and extending the life of moving parts subject to wear.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	SAE 30
Specific gravity at 15 c	0.87
Viscosity at 40c, mm ² /s (cSt)	95
Viscosity 100c, mm ² /s (cSt)	10.5
Viscosity index	109
TBN, mgKOH/g	5.8
Flash Point C	227

PACKAGE SIZE 5 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.