



PRODUCT DATA SHEET

HI-VIS 70

Automotive Engine Oil

SAE 70 SG/CC

Code:116

HI-VIS 70 is a specially blended high viscosity engine oil containing detergent additives, corrosion inhibitors, anti-oxidants and anti-wear agents

SPECIFICATIONS

HI-VIS 70 meets or exceeds the following specifications.

- API SG/CD
- SAE 70
- CCMC G1,G2, D1

APPLICATIONS

HI-VIS 70 is suitable for use in all older vehicles that specify an SG rated oil. This incorporates those operating on L.P.G.

HI VIS 70 has exceptional viscosity characteristics which makes it very suitable for engines with very low pressure and/or high oil consumption.

HI VIS 70 will also help to reduce engine noise caused by extremely worn parts and is ideally suited for use in 4 stroke motor cycle engines.

HI-VIS 70 is also suitable for use in diesel engines requiring A.P.I. CD performance.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	25W50
Specific gravity at 15 c	0.91
Viscosity at 40c, mm ² /s (cSt)	290
Viscosity 100c, mm ² /s (cSt)	27.5
Viscosity index	126
TBN, mgKOH/g	5.8
Flash Point C	227

PACKAGE SIZE 5 & 20 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.