



PRODUCT DATA SHEET

MULTIVIS

Automotive Engine Oil

25W50 SG/CC

Code:120

MULTIVIS is a service fill petrol engine oil blended using high quality base stocks and additives to produce an oil with excellent stay in grade properties.

SPECIFICATIONS

MULTIVIS meets or exceeds the following specifications

- API SG/CC
- SAE 25W50
- CCMC G2
- US MILITARY - MIL-L-46152C

APPLICATIONS

MULTIVIS is suitable for the lubrication of all types of cars, light commercials and small diesel engines where a SG petrol rating or CC diesel rating is required.

MULTIVIS is also suitable for L.P.G. powered vehicles and in all pre 1989 passenger cars requiring a 25W50 oil will provide your engine with the maximum amount of protection required.

MULTIVIS meets or exceeds the requirements of an SG/CC engine oil and will provide a high level of protection against engine deposits, oil oxidation, wear, sludge formation and acid corrosion.

MULTIVIS assists in maintaining engine cleanliness.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	25W50
Specific gravity at 15 c	0.9
Viscosity at 40c, mm ² /s (cSt)	195
Viscosity 100c, mm ² /s (cSt)	18
Viscosity index	101
TBN, mgKOH/g	5.8
Sulphated ash %	0.85

PACKAGE SIZE 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.